



50 MHz Analog-Oscilloscope HM 504-2

Autoset, Save/Recall, Readout/Cursor and RS-232 Interface

- 2 Channels, DC-50 MHz, 1 mV-20 V/div, Component Tester
- Triggering DC - 100 MHz (autom. Peak to Peak) ≥ 0.5 div
- Time Base 0.5 s - 10 ns/div, with Delay and 2nd Trigger
- Automatic Measuring Functions, Built in Adjustment Menu
- 100 MHz Frequency & Period Counter, 4 Digit Resolution

The new **50 MHz** analog oscilloscope **HM 504-2** unsurpassed in its price range, demonstrated by its high performance measurement characteristics and ease of operation. Other outstanding features are the integrated **100 MHz** frequency counter and five automatic voltage measurement functions.

The frequency response of the 50 MHz (-3 dB) Y-amplifiers allows signal displays higher than **100 MHz**. Delayed time base operation allows high resolution analysis of asynchronous and complex signals simple in free run mode or in combination with the independent **second trigger circuit**. Briefly pressing the **Autoset** button results in an automatic, optimum setting of the controls for almost any signal to get a **fast signal presentation**. **Save/Recall** offers 9 non volatile memories for complete parameter set ups, which may be stored and recalled randomly. Another feature is the built in **RS-232**

interface for control purposes via a PC including convenient **free PC software**. New in this price-performance class is the high- and low frequency adjustable probes. With the built in calibrator, checking of the instrument's transient response characteristics is an easy task.

Front panel settings and selected features are alphanumerically displayed on the screen (**Readout**). For example, the results of cursor independent automatic measurement of frequency, period, dc and ac voltages. **Voltage, time, frequency, phase angle, gain, rise time, ratio X and ratio Y** can be determined by manual cursor measurement. The **HM 504-2** also offers XY and component test mode, a **built in adjustment menu** for closed case calibration of the vertical, trigger and storage amps, a **Calibrator (1 Hz - 1 MHz)** for probe and time base check, and Z-modulation.

Accessories supplied:

Operators Manual and PC-Software on CD-ROM, 2 Probes 1:1/10:1 and Line Cord.

Specifications

Ref. Temperature: 23°C ±2°C

Vertical Deflection

Operating modes:	CH I or CH II separate CH I and CH II alternate or chopped (0.5MHz)
Sum or Difference:	from CH I and CH II
Invert:	CH II
XY-Mode:	via CH I (X) and CH II (Y)
Frequency range:	2x DC - 50MHz (-3dB)
Rise time, Overshoot:	<7ns, ≤ 1%
Deflection coefficient:	14 calibrated steps (1-2-5 sequence)
1mV-2mV/div:	±5% DC to 10MHz (-3dB)
5mV-20V/div:	±3% DC to 50MHz (-3dB) with variable >2.5:1 (uncal.) to >50V/cm
Input impedance:	1 MΩ 18pF
Input coupling:	DC-AC-GD (ground)
Input voltage:	max. 400V (DC + peak AC)

Triggering

Automatic (peak to peak):	≥ 0.5div, 20Hz – 100MHz
Normal with level control:	≥ 0.5div, 0 - 100MHz
Indicator for trigger action:	LED
Slope:	positive or negative
Sources:	CH I or II, alternate CH I and CH II (≥ 0.8div), line (mains) and external
Coupling:	AC (10Hz - 100MHz) DC (0 - 100MHz) HF (50kHz - 100MHz) LF (0 - 15kHz)
2nd Triggering:	normal with level control and slope selection
External:	≥ 0,3Vpp (0 - 50MHz)
Active TV Sync Separator:	field and line, pos. and neg.

Horizontal Deflection

Time coefficients:	22 calibrated steps (1-2-5 sequence), 0.5s/div – 50ns/div (± 3%), with variable >2.5:1(uncal.) to >1.25s/div
Delay:	140ms – 200ns (variable)
Hold off time:	variable to approx. 10:1
Bandwidth X-Amplifier:	0 - 3MHz (-3dB)
X-Y phase shift:	<3° below 120kHz

Operation / Display

Manual / Autoset:	front panel switches / autom. parameter selection
Save/Recall:	9 user defined instrument settings
Readout:	display of instrument settings automatic measuring results Cursor measurement results mathematic calculation results and pull down menus
Frequency counter:	4 digit (0,01% ±1 digit) 0.5 Hz - 100 MHz
Interface (standard fitting):	RS-232 (for control)
Option:	control data via glass fiber: HZ70

Component Tester

Test voltage, frequency:	approx. 7Vrms (open circuit), approx. 50Hz
Test current:	approx. 7mA _{rms} (short circuit) One test lead is grounded (Safety Earth)

General Information

CRT:	D14-363GY, 8x10cm, internal graticule
Acceleration voltage:	approx. 2kV
Z-Input (Intens. modulation):	max. +5V (TTL)
Calibrator (square wave):	0.2V ±1 %, 1 Hz to 1MHz (tr <4ns), DC
Trace Rotation:	adjustable on front panel
Line voltage:	100-240V AC ±10%, 50/60Hz
Power consumption:	approx. 34 Watt at 50Hz.
Min./Max. ambient temperature:	10°C...+40°C
Protective system:	Safety class I (EN 61 010, IEC 1010-1)
Weight:	ca. 5.4kg
Color:	techno-brown
Cabinet (W x H x D):	285 x 125 x 380 mm

Accessories supplied:

Operators Manual and PC-Software on CD-ROM, 2 Probes 1:1/10:1 and Line Cord.